Server Comp'r

Data Mgmt

132

130

120

Communi-cations Link

107

Heat Balance Server

OPS & Maint. Cost

109

111 Browser

112 Server Component

113 Analysis Component

114 File Wrapper

115 Routines

110

Analysis scrips, data files...

file wrapper

Plant Economic Server

Costing Model Server

Component Lifting Server

Heat Transfer Server

Secondary Flow Server

Bottoming Cycle Server

GT Performance Server

101

102

106

103

104

105

108

Fig. 1

Fig. 2

Fig. 3

GT Simulator - Communication between Core Components

Secondary Flow Analysis — 103

Choked and Unchoked Compressible Flow equations, plus design information about all cooling and leakage networks and areas

PERFORMANCE ANALYSIS — 102

T_{cd}, P_{cd}, $Pbleed_{1-2}$, $Tbleed_{1-2}$

Total Internal Flows, Flow distribution by stage

Total Internal flows Flow distribution by stage

Flowpath boundary condition pressures

Turbine Aerodynamic Analysis — 101

Stage-by-stage power and efficiency
Interstage temperatures and pressures

Compressor

Combustor

Expand'r — 308

306

304

T_{bleed_2} P_{bleed_2}

T_{bleed_1} P_{bleed_1}

T_{cd} P_{cd}

P_t, T_{fire}, P_{exit}

300

308

P_{exit}

Exit Guide Vanes

P_s, P_t, T_s

$B3$ 3-2 (3-2a) 3-1a

T_{t_3} 3-1 3-0 N3

323

P_s, P_t, T_s

$B2$ 2-2 (2-2a) 2-1a

T_{t_2} 2-1 2-0 N2

322

P_s, P_t, T_s

$B1$ 1-2 (1-2a) 1-1a

332

321

T_{fire} 1-1 1-0 N1 331

P_t

Fig. 4

Inner Loop Start

502
$i = 1$

504
Perf. module determines:
P_{t_i}, T_{fire_i}, P_{EXIT_i}

506
Perf. module x-fer P_{t_i}, T_{fire_i}, P_{EXIT_i} to aero. module

508
Aero. module determines:
interstage variables, stage powers and stage efficiencies

510
Aero. module x-fer interstage variables, etc., to perf. module

512
Perf. module updates model and determines:
$P_{t_{i+1}}$, $T_{fire_{i+1}}$, $P_{EXIT_{i+1}}$

514
Compare:
$P_{t_{i+1}} \rightarrow P_{t_{i-1}}$
$T_{fire_{i+1}} \rightarrow T_{fire_{i-1}}$
$P_{EXIT_{i+1}} \rightarrow P_{EXIT_{i-1}}$

516
Are values w/i specified error %?

No

520
$i = i+1$

Yes

518
Perf. module and aero. module determine perf. parameters and provide to other analysis modules

500

Fig. 5

Routine Complete

Outer Loop Start

602

$i = 1$

604

Perf. module and aero. module perform inner loop; determine variables including P_{t_i}, T_{fire_i}, P_{EXIT_i}

606

Perf. module and aero. module provide secondary flow parameters and flow path boundary condition pressures to sec'dy flow module

608

Sec'dy flow module determines internal flow distribution var.

610

Sec'dy flow module x-fer internal flow distri. variables to perf. module and aero. module

612

Perf. module and aero. module update models w/data from sec'dy flow module

613

Perf. module determines: $P_{t_{i+1}}$, $T_{fire_{i+1}}$, $P_{EXIT_{i+1}}$

600

614

Compare:
$P_{t_{i+1}} \rightarrow P_{t_i}$
$T_{fire_{i+1}} \rightarrow T_{fire_i}$
$P_{EXIT_{i+1}} \rightarrow P_{EXIT_i}$

620

$i = i+2$

618

Perf. module, aero. module and sec'dy flow module provide parameters to other analysis modules

Yes

616

Are values w/i specified error %?

No

Routine Complete

Fig. 6

Fig. 7

GT Simulation Control Panel

☑ Show Iteration History
☑ Show Convergence Summary
☑ Show Output Summary

☐ Clear History [Inactive] | Record Iteration

Iteration History

Iteration Status: Iterate2 Complete

Loop 2 (Outer Loop: Secondary Flow->CycleDeck->Iterator1)

Time Started (Loop2)	6/18/03 11:05:50
+Time Started (Cooling Analysis)	6/18/03 11:05:50
-Time Completed (Cooling Analysis)	6/18/03 11:06:02
+Time Started (Cycle Deck)	6/18/03 11:06:19
-Time Completed (Cycle Deck)	6/18/03 11:06:48
+Time Started (Iterator 1)	6/18/03 11:07:05
-Time Completed (Iterator 1)	6/18/03 11:13:06
-Time Completed (Loop2)	6/18/03 11:13:07

9FA+e SF Sys YFT

Run Time (Cooling Analysis) [sec]	12
Run Time (Cycle Deck) [sec]	29
Run Time (Iterator 1) [sec]	361
Run Time (Other Calculation) [sec]	36
Run Time (Loop2 Total) [sec]	43
Iteration # (Loop 2)	1

Loop 1 (Inner Loop: TP3->CycleDeck)

Time Started (Loop1)	6/18/03 11:07:06
+Time Started (TP3)	6/18/03 11:07:06
-Time Completed (TP3)	6/18/03 11:12:01
+Time Started (Cycle Deck)	6/18/03 11:12:18
-Time Completed (Cycle Deck)	6/18/03 11:12:47
Time Completed (Loop1)	6/18/03 11:13:06

Run Time (Other Calculation) [sec]	360
Run Time (Loop1 Total) [sec]	360
Iteration # (Loop 1)	1

| Iteration # (Loop 2) | 1 |
| Iteration # (Loop 1) | 1 |

Variable Name

Convergence(Percent Difference)	
SysLoop1.TP3vsCD_Dpct_ETA_TT_1	0.00
SysLoop1.TP3vsCD_Dpct_ETA_TT_2	0.00
SysLoop1.TP3vsCD_Dpct_ETA_TT_3	0.00
SysLoop1.TP3vsCD_Dpct_PRATIO_TT_T1	0.00
SysLoop1.TP3vsCD_Dpct_PRATIO_TT_T2	-0.01
SysLoop1.TP3vsCD_Dpct_PRATIO_TT_T3	0.01
SysLoop1.TP3vsCD_Dpct_WN1exit	-0.02
SysLoop1.TP3vsCD_Dpct_WN2exit	-0.03
SysLoop1.TP3vsCD_Dpct_WN3exit	-0.02
SysLoop1.TP3vsCD_Dpct_HP_T1	-0.12
SysLoop1.TP3vsCD_Dpct_HP_T2	-0.11
SysLoop1.TP3vsCD_Dpct_HP_T3	-0.09
SysLoop1.TP3vsCD_Dpct_HP_Total	-0.10

Output Summary

Ambient Conditions

Temperature	59	[degF]
Pressure	14.7	[psia]
Relative Humidity	60	[%]

GT Result Summary (per GT)

Exhaust Pressure Loss	15	[in of H2O]
Fuel Heating Value (LHV)	4,369	[Btu/lbm] LHV
Fuel Temperature	80	[degF]
GT Output	290,000	[kW]
GT Heat Rate (LHV)	8,725	[Btu/kW-hr] LHV
Heat Consumption (LHV)	2750.45	[10^6 Btu/hr] LHV
Exhaust Flow	1647.25	[pps]
Exhaust Temperature	1099.7	[degF]

CC Plant Result Summary

GT Output (Total)		[kW]
ST Output		[kW]
CC Gross Power Output		[kW]
CC Auxiliary Power		[kW]
CC Net Power Output		[kW]
CC Net Heat Rate (LHV)		[Btu/kW-hr] LHV
CC Net Efficiency (LHV)		[%] LHV

Convergence Summary

MaxOfErr(allow < 0.15%) = 0.12 %
SumOfErr(allow < 999%) = 0.57 %
Last Iteration (Limit = 1) = 1

Inner Loop Convergence Check

Variable	Description	%Diff	Cyc Deck	TP3
ETA_TT_1	Turbine xth Stg Efficiency (t-t)	0.00	0.8851	0.8851
ETA_TT_2	ETA_TT_Tx	0.00	0.8806	0.8806
ETA_TT_3		0.00	0.8879	0.8879
PRATIO_TT_T1	Turbine xth Stg Press Ratio (t-t)	0.00	2.099	2.099
PRATIO_TT_T2	PRATIO_TT_Tx	-0.01	2.031	2.031
PRATIO_TT_T3		0.01	2.817	2.817
WN1exit	Turbine Stg y nozzle exit flow	-0.02	1477.4	1477.7
WN2exit	WN1yexit	-0.03	1582.2	1582.6
WN3exit		-0.02	1620.9	1621.3
HP_T1	Horse power of Turbine Stg x	-0.12	278098	278395
HP_T2	HP_Tx	-0.11	264413	264673
HP_T3		-0.09	254894	255099
HP_Total	Total Turbine HP	-0.10	797395	798166.9
WExhaust	Turbine exhaust flow (after B3 dilution)	-0.02	1638.84	1639.2
PTTinlet	Total Pressure at Turbine inlet (just u	-0.02	229.4	229.44
PTTexit	Total Pressure at Turbine exit (before)	-0.02	16.142	16.146
TP3 Run Status	Normal Termination	OK		

Outer Loop Convergence Check

MaxOfErr(allow < 0.1%) = 0.02 %
SumOfErr(allow < 999%) = 0.26 %
Last Iteration (Limit = 4) = 1

Variable	Description	%Diff	Curr ltr	Prev ltr
Prev.CD.w2	Compressor air flow [pps]	-0.02	1433.60	1434.14
Prev.Wnch	Non chargeable flow rate	-0.01	12.075	12.077
Prev.Wch.CD	Chargeable flow extracted from 18th S	-0.01	2.9960	2.9662
Prev.Wch.17th	Chargeable flow extracted from 17th S	-0.01	4.1000	4.1050
Prev.Wch.13th	Chargeable flow extracted from 13th S	0.01	2.2371	2.2369
Prev.Wch.9th	Chargeable flow extracted from 9th S	0.02	0.1519	0.1519
Prev.CD.WExhaust	Exhaust flow (after B3 dilution, before	-0.02	1658.84	1659.22
Prev.CD.WN1exit	Turbine Stg 1 nozzle exit flow	-0.02	1477.37	1477.72
Prev.CD.WN2exit	Turbine Stg 2 nozzle exit flow	-0.02	1582.21	1582.56
Prev.CD.WN3exit	Turbine Stg 3 nozzle exit flow	-0.02	1610.94	1611.33
Prev.CD.PTinlet	Total Pressure at Turbine inlet (just u	-0.02	229.40	229.44
Prev.CD.PTTexit	Total Pressure at Turbine exit (before	-0.02	16.14	16.15
Prev.CD.Pcd	Compressor discharge total pressure	-0.02	244.84	244.89
Prev.CD.Tcd	Compressor discharge total temperat	-0.01	785.10	785.20
Prev.CDdervied HP	Total Horse power of Turbine Stg 1-3	-0.02	717395	717513

Power Plant Configuration

GE STAG 207FA+e (7x1)

GT Inlet Type Options
- Option 1: None
- Option 2: None
- Option 3: None

Analysis Options
- ○ Single Inner Loop (Cycle Deck -> TP3)
- ○ Iterate Inner Loop (Cycle Deck <-> TP3)
- ○ Single Outer Loop (Flow->CycleDeck<->TP3)
- ◉ Iterate Outer Loop (Flow<->CycleDeck<->TP3)

☑ Record Results in History   ☐ Finish Analysis w/ MHB, HiBal

Iteration Status Iterate2 Complete

[Execute Analysis]

Spreadsheets Hide Options
- ☐ Hide YFT Spreadsheets
- ☐ Hide Cooling Spreadsheets
- ☐ Hide TP3 Spreadsheets
- ☐ Hide CycleDeck, MHB, HeatBal Spreadsheets
- ☐ Hide Gas temp Spreadsheets (Under Construction)
- ☐ Hide Lifing Spreadsheets (Under Construction)
- ☐ Hide Convergence Spreadsheets
- ☐ Hide Misc Spreadsheets

[Hide All]   [UnHide All]

Data Files

	Default Filenames
Cycle Deck Output	tp3.in
TP3 Input	tp3.in
TP3 Standard Out	stdout
TP3 Detail Out	tp3.out
TP3 Quick Summary Out	quick.sum

[Save Data Files]

YFT Execution Options
Available YFT Models:
- ☑ Use HPP YFT Model
- ☐ Use S1S YFT Model
- ☑ Use S2N YFT Model
- ☑ Use S3N YFT Model
- ☑ Use ROTOR YFT Model

☐ Execute YFT In Loop

Convergence Control Options
Inner Loop Convergence Criterias
Max Allow Err (def=0.15) | 0.15 | %
Max Allow Sum of Err (def=999) | 999.00 | %
Max Iterations (def=2) | 1 |

Perf. | Aero | Cooling

Convergence History:

Tolerance for convergence:	0.1		
Max number of iterations:	8		
Number of matching B.C.'s:	11		

Convergence History chart — iteration error (100.00, 10.00, 1.00) vs. iteration number (1–8); data points 31.35 and 5.09

Flow path	variable	model	type	ID	1 (31.35)	2 (5.09)	3	4	5	6	7	8	9	10
		Iteration Error			31.35	5.09								
1 — 1SXOVL	P	S2N		1	100.00	99.00								
		S1S		3	102.00	100.00								
	T	S2N		1	700.00	690.00								
		S1S		3	650.00	645.00								
	Flow	S1S	1SXOVL	117	0.2000	0.1800								
		S2N		117	0.2000	0.1990								
2 — 2STOTL	P	S2N		1	100.00	99.00								
		S3N		1	90.00	91.00								
	T	S2N		1	700.00	690.00								
		S3N		1	600.00	595.00								
	Flow	S3N	2STOTL	118	0.5000	0.4500								
		S2N		118	0.3000	0.2900								
3 — 1BSHKT	P	S2N		14	300.00	296.00								
		HPPS		20	60.00	59.00								
	T	S2N		14	950.00	949.00								
		HPPS		20	700.00	698.00								
	Flow	HPPS	1BSHKT	62	0.1500	0.1400								
		S2N		62	0.2000	0.1990								
4 — 1RAFTL	P	S2N		15	100.00	98.00								
		ROTORF		22	80.00	79.00								
	T	S2N		15	710.00	702.00								
		ROTORF		22	800.00	801.00								
	Flow	ROTORF	1RAFTL	64	0.5000	0.4900								
		S2N		64	0.2100	0.2000								
5 — 1BDTAL	P	S2N		15	101.00	100.00								
		ROTORF		22	90.00	89.00								
	T	S2N		15	800.00	798.00								
		ROTORF		22	805.00	801.00								
	Flow	ROTORF	1BDTAL	77	0.5000	0.4800								
		S2N		77	0.3000	0.2200								
6 — 2RFWDL	P	S2N		21	50.00	48.00								
		RO ORF		31	50.00	51.00								
	T	S2N		21	900.00	860.00								
		ROTORF		31	800.00	830.00								
	Flow	ROTORF	RFWDL	65	0.3500	0.3000								
		S2N		65	0.2000	0.1800								

Reference labels: 800, 802, 803, 804, 806, 807, 808, 809

Fig. 8

TP3 Settings

Fig. 9

902 — TP3 Settings

TP3 Areas (linked or unlinked): unlinked

Orange values need updating before use!

	UNIT	7FA		6FA	7F	7FA		7FA+	7FA+e
RPM	Sysin RPM	3600		5254	3600	3600	S1N	3600	3600
Frame Scale Factor	SF	1		1	1	1	S1S	1	1
							S1B		
							S2N		
							S2S		
							S2B		
							S3N		
							S3S		
							S3B		

S1N

	UNIT	7FA	6FA	7F	7FA	7FA+	7FA+e
roughness	CLAKV_STG1	30	10	20	30	40	50
inlet metal angle	SDIA_STG1	7	4	6	7	10	12
throat area	SPA_STG1	20	16	18	20	22	24
TE thickness	TEV_STG1	20	0	10	20	30	40

Orange values need updating before use!

S1S

	UNIT	7FA	6FA	7F	7FA	7FA+	7FA+e
tip clearance	TCL_STG1	0.4	0.3	0.4	0.4	0.2	0.8

S1B

	UNIT	7FA	6FA	7F	7FA	7FA+	7FA+e
surface roughness	CLAKB_STG1	200	200	200	200	200	200
inlet metal angle	RDIA_STG1	14	10	12	14	16	18
throat area	RPA_STG1	100	100	100	100	100	100
TE thickness	TEB_STG1	0.2	0.2	0.2	0.2	0.2	0.2

S1 Data Match Adjusters

	UNIT	7FA	6FA	7F	7FA	7FA+	7FA+e
flow coefficient (S1N)	SCF_STG1	0.6	0.4	0.5	0.6	0.7	0.8
flow coefficient (S1B)	RCF_STG1	1	1	1	1	1	1
efficiency (S1N)	DETAV_STG1	0	0	0	0	0	0.2
efficiency (S1B)	DETAB_STG1	0	0	0	0	0	0.2

S2N

	UNIT	7FA	6FA	7F	7FA	7FA+	7FA+e
roughness	CLAKV_STG2	30	10	20	30	40	50
inlet metal angle	SDIA_STG2	7	4	6	7	10	12
throat area	SPA_STG2	30	26	28	30	32	34
TE thickness	TEV_STG1	20	0	10	20	30	40

Orange values need updating before use!

S2S

	UNIT	7FA	6FA	7F	7FA	7FA+	7FA+e
tip clearance	TCL_STG2	0.4	0.3	0.4	0.4	0.2	0.8

S2B

	UNIT	7FA	6FA	7F	7FA	7FA+	7FA+e
surface roughness	CLAKB_STG2	100	100	100	100	100	100
inlet metal angle	RDIA_STG2	14	10	12	14	16	18
throat area	RPA_STG2	180	180	180	180	180	180
TE thickness	TEB_STG1	0.2	0.2	0.2	0.2	0.2	0.2

906, 904, 908, 900